AsktheBuilder.com

Deck Stain Test Results
Released April 14, 2013

Early Spring 2013



(c) Copyright 2013 Tim Carter - All Rights Reserved

It's ILLEGAL to republish, reprint, resell, rent or otherwise distribute these test results.

Introduction:

Each year I receive hundreds of emails from frustrated consumers. They're all looking for the deck sealer / stain that offers the best performance - they're looking for the Holy Grail of deck sealers.

I decided I'd do a side-by-side test of as many deck stains / sealers that I could get my hands on.

On May 12, 2012 thirty-two pieces of cedar decking and thirty-two pieces of regular treated lumber were stained with off-the-shelf wood deck stains / sealers.

Sixteen different wood sealers / stains were used to coat the lumber creating two identical sample sets. One set was immediately exposed to the weather and the other set was boxed up and stored indoors away from sunlight and all weather.

The control pieces placed in the box were to be used in a series of photographs to show how the deck stains performed after the other pieces weathered for nearly a year.

Every brand name deck sealer company was contacted to participate in this real-life test. *Many companies refused to participate in the test.*

I am planning to do a comprehensive test of all brands starting in early May of 2013. I'll purchase the brands that refuse to send samples for testing.

The following manufacturers submitted product in April 2012:

TWP, Armstrong's, Defy, Behr, Benjamin Moore, Wolman's, Sherwin Williams, Olympic, and Thompson's. Some manufacturers submitted different blends and colors for the test.

Photo Legend and Test Conditions:

As you look at each photo, you'll see the wider cedar decking on the left and the shorter and narrower pieces of treated pine lumber on the right.

The pieces of wood that were exposed to the weather have two screw holes in each one as they were screwed to a flat 2x4 to simulate resting on a floor joist. They're the left-side samples of each pair (except in sample B where the treated lumber left outdoors is on the far right).

The pieces of wood exposed to the weather were set out on my dock on Lake Winnisquam in central New Hampshire. The shore line faces east, so the boards experienced brutal sunlight from dawn until mid-late afternoon.



The pieces of wood were set side-by-side on the dock separated by maybe 3 inches. In other words, the cedar and treated lumber each received identical amounts of sun, rain and shade.





To discover what deck sealer was used in the photo click here:



To discover what deck sealer was used in the photo click here:



























http://go.askthebuilder.com/DeckStainTestResults

That's it for this test! Watch for the 2014 results when I test even MORE products! Thanks and I hope you have a new respect for the different deck sealers.

Tim Carter – Founder www.AsktheBuilder.com

Do It Right, Not Over.